

KONICA MINOLTA Bizhub 454e (554e / 654e / 754e)

Viteza A4/A3: 45(55/65/75)/22 (27/33/37) ppm
alb-negru

Formate hartie: A6-SRA3, formate customizate si
format banner de pana la 1,2 m lungime

Panou tactil, color de 9 inch cu functionalitati
multi-touch

Alimentatorul dual de documente scaneaza
ambele fete ale originalelor dubla fata la o singura trecere
la viteza de 160 ipm

Finisare modulara si optiuni ale tavilor de
alimentare pentru configuratii customizate



Imaginea este cu titlu de prezentare

Sisteme de operare



Specificatii copiator

Proces copiere	Copiere electrostatica laser
Sistem toner	Simitri™ - toner polimerizat
Viteza copiere/printare A4 alb negru	Pana la 45 ppm
Viteza copiere/printare A3 alb negru	Pana la 22 ppm
Viteza duplex A4 alb negru	Pana la 45 ppm
Prima pagina copiata/printata alb negru	4.6 sec
Timpul de incalzire	Aprox. 25 sec * Timpul de incalzire poate varia in functie de mediul ambiant
Rezolutie copiere	600 x 600 dpi
Gradatii	256 gradatii
Copiere multipla	1 - 9,999
Format documente originale	A5 - A3 25-400% in pasi de 0.1%; zoom automat
Marire-micsorare	Capitol; inserare pagina si capitol; copie de test (print si ecran); ajustare test de print; functii arta digitala; memorare setari joburi; mod poster; repetare imagine; overlay (optional); stampilare; protejare la copiere
Functii copiere	

Specificatii imprimanta

Rezolutie printare	1,800 x 600 dpi; 1,200 x 1,200 dpi
Limbaje printare	PCL6 (XL 3.0); PCL 5; PostScript 3 (CPSI 3016); XPS

Sisteme operare

Windows XP (32/64)
Windows VISTA (32/64)
Windows 7 (32/64)
Windows 8 (32/64)
Windows Server 2003 (32/64)
Windows Server 2008 (32/64)
Windows Server 2008 R2 (64)
Windows Server 2012 (64)

Fonturi printare

Macintosh OS X 10.x
Unix, Linux, Citrix
80 PCL Latin; 137 PostScript 3
Emulation Latin

Functii printare

Printare directa PCL, PS, TIFF, XPS, PDF, fisiere PDF criptate si OOXML (DOCX, XLSX, PPTX); mixmedia si mixplex; programare joburi "Easy Set"; overlay; watermark; protejare copiere; carbon copy print

Specificatii scanner

Viteza scanare alb negru	Pana la 160 ipm
Rezolutie scanare	Max.: 600 x 600 dpi
Moduri scanare	Scan-to-eMail (Scan-to-Me) Scan-to-SMB (Scan-to-Home) Scan-to-FTP Scan-to-Box Scan-to-USB Scan-to-WebDAV Scan-to-DPWS Scanare TWAIN in retea
Formate fisier	JPEG; TIFF; PDF; PDF/A 1a si 1b (optional); PDF compact; PDF criptat; PDF indexabil (optional); XPS; XPS compact; PPTX; PPTX indexabil (optional); DOCX/XLSX indexabil (optional)

Destinatii scanare	2,100 (utilizatori + grupuri); suport LDAP	Duplex automat	A5-SRA3; 52-256 g/m ²
Functii scanare	Adnotare (text/timp/data) pentru PDF; pana la 400 programe joburi; previzualizare scanare in timp real	Moduli finisare (optional)	Offset; grupare; sortare; capsare; perforare; post inserare; pliere mediana; pliere in forma de scrisoare; brosurare
Specificatii fax		Capacitate iesire (cu finisher)	Max.: 3,300 coli
Standard fax	Super G3 (optional)	Capacitate iesire (fara finisher)	Max.: 250 coli
Transmisie fax	Analog		Max.: 50 coli sau 48 coli + 2 coperti (pana la 209 g/m ²)
	i-Fax	Capsare	
	i-Fax color (RFC3949-C)	Capacitate iesire la capsare	Max.: 1,000 coli
	IP-Fax	Pliere in forma de scrisoare	Pana la 3 coli
Rezolutie fax	Max.: 600 x 600 dpi (ultra-fine)	Capacitate coli pliate in forma de scrisoare	Max.: 30 coli (tava); nelimitat
Compresie fax	MH; MR; MMR; JBIG		Max.: 20 coli sau 19 coli + 1 coperta (pana la 209 g/m ²)
Modem fax	Pana la 33.6 Kbps	Brosura	Max.: 100 coli (tava); nelimitat
Destinatii fax	2,100 (utilizatori + grupuri)	Capacitate iesire brosură	
	Polling; transmisie intarziata; PC-Fax; receptie confidentiala in box; Receptie pe e-mail/FTP/SMB; pana la 400 programe joburi	Volum copiere/printare recomandat (lunar)	30000
Functii fax		Volum copiere/printare maxim (lunar)	60000
Specificatii user box		Durata viata toner Black	29280
Nr. maxim documente care se pot stoca	Pana la 3,000 documente sau 10,000 pagini	Durata viata unitate imagine Black	130,000 pagini/600,000 pagini (Drum/Developer)
Tipuri de user box	Public	Consum energie	220-240 V / 50/60 Hz; Mai putin de 2.0 kW (sistem)
	Personal (cu parola sau autentificare)	Dimensiuni sistem (Lxhxh)	615 x 685 x 921 mm (fara ADF si casete suplimentare)
	Grupuri (cu autentificare)	Greutate sistem	Aprox. 93 kg
Tipuri de boxuri sistem	Printare securizata	Functii sistem	
	Printare PDF criptat		ISO 15408 EAL3 (in evaluare); conform IEEE 2600.1; filtrare IP si blocare porturi;
	Receptie fax		criptare comunicare in retea SSL2; SSL3 si TSL1.0;
	Fax polling		suport IPsec; suport IEEE 802.1x; autentificare utilizatori;
Functionalitati user box	Reprintare; combinare		raport autentificare; printare securizata; suprascriere hard disk (8 tipuri standard);
	Descarcare		criptare date pe hard disk (AES 128);
	Trimitere (e-mail/FTP/SMB si fax)		stergere automata a datelor din memorie; receptionare confidentiala a faxurilor;
	Copiere din box in box		Criptarea datelor de printare; protectie la copiere (Copy Guard, Password Copy) optional
Specificatii sistem			
Memorie sistem standard	2048 MB	Securitate	
Hard disk sistem standard	250 GB		
Interfete standard	10-Base-T/100-Base-T/1,000-Base-T Ethernet, USB 2.0		
Protocoale de retea	TCP/IP (IPv4 / IPv6); IPX/SPX; NetBEUI; AppleTalk (EtherTalk); SMB; LPD; IPP; SNMP; HTTP		
Tipuri frame-uri	Ethernet 802.2; Ethernet 802.3; Ethernet II; Ethernet SNAP		
Alimentator automat documente	Pana la 100 originale; A6-A3; 35-163 g/m ²	Contorizare	Pana la 1,000 conturi utilizatori; suport Active Directory (nume utilizator + parola + e-mail + folder smb)
Format hartie	ADF dualscan		Definire acces utilizatori
	A6-SRA3, formate hartie particularizate;		Autentificare biometrica (scanarea dispunerii venelor in sange) optional
Greutate hartie	hartie banner max. 1,200 x 297 mm		Autentificare prin card IC-Card (cititor IC-Card) optional
Capacitate alimentare hartie	52-300 g/m ²		
	Standard: 1150 coli		
	Max.: 6650 coli		
Casete hartie standard	Caseta 1: 500 coli, A5-A3, 52-256 g/m ²		
	Caseta 2: 500 coli, A5-SRA3, 52-256 g/m ²		
	Alimentare manuala (bypass): 150 coli, A6-SRA3, dimensiuni particularizate, banner, 60-300 g/m ²		
Specificatii hartie optional	Caseta 3: 500 coli, A5-A3, 52-256 g/m ²	Software	PageScope Net Care Device Manager
	Casetele 3 + 4: 2 x 500 coli, A5-A3, 52-256 g/m ²		PageScope Data Administrator
	Caseta de mare capacitate: 2,500 coli, A4, 52-256 g/m ²		PageScope Box Operator
	Caseta alimentare de mare capacitate (1): 3,000 coli, A4, 52-256 g/m ²		PageScope Direct Print
	Caseta alimentare de mare capacitate (2): 2,500 coli, A4-SRA3, 52-256 g/m ²		Print Status Notifier
			Driver Packaging Utility
			Log Management Utility