

## KONICA MINOLTA Bizhub C224e

Viteza A4/A3: 22/14 ppm color si alb-negru  
Formate hartie: A6-SRA3, formate customizate si format banner de pana la 1,2 m lungime  
Panou color, tactil, de 9 inch cu functionalitate multi-touch  
Alimentatorul de documente dual-scan scaneaza intr-o singura trecere ambele fete ale originalelor printate fata-verso, la viteza de 160 ipm  
Finisare modulara si optiuni ale tavilor de alimentare pentru configuratii customizate

### Sisteme de operare



### Specificatii copiator

Proces copiere	Copiere electrostatica laser tandem indirecta
Sistem toner	Toner polimerizat Simitri HD®
Viteza copiere/printare A4 alb negru	22 cpm
Viteza copiere/printare A4 color	22 cpm
Viteza copiere/printare A3 alb negru	14 cpm
Viteza copiere/printare A3 color	14 cpm
Viteza duplex A4 alb negru	22 cpm
Viteza duplex A4 color	22 cpm
Prima pagina copiata/printata alb negru	6.9 sec
Prima pagina copiata/printata color	8.3 sec
Timpul de incalzire	Aprox. 20 sec * Timpul de incalzire poate varia in functie de mediul ambiant
Rezolutie copiere	600 x 600 dpi
Gradatii	256 gradatii
Copiere multipla	1-9,999
Format documente originale	A5-A3
Marire-micsorare	25-400% in pasi de 0.1%; zoom automat
Funcții copiere	Capitol; inserare pagina si capitol; copie de test (print si ecran); ajustare test de print; functii arta digitala; memorare setari joburi; mod poster; repetare imagine; overlay (optional); stampilare; protejare la copiere

### Specificatii imprimanta

Rezolutie printare	1,800 x 600 dpi 1,200 x 1,200 dpi
Procesor	800 MHz
Limbaje printare	PCL6 (XL 3.0) PCL 5c PostScript 3 (CPSI 3016) XPS
Sisteme operare	Windows XP (32/64) Windows VISTA (32/64) Windows 7 (32/64) Windows 8 (32/64) Windows Server 2003 (32/64) Windows Server 2008 (32/64) Windows Server 2008 R2 (64) Windows Server 2012 (64) Macintosh OS X 10.x Unix, Linux, Citrix
Fonturi printare	80 PCL Latin; 137 PostScript 3 Emulation Latin
Funcții printare	Printare directa PCL, PS, TIFF, XPS, PDF, fisiere PDF criptate  si OOXML (DOCX, XLSX, PPTX); mixmedia si mixplex; programare joburi "Easy Set"; overlay; watermark; protejare copiere; carbon copy print

### Specificatii scanner

Viteza scanare color	Pana la 160 ipm (cu DF-701 optional)
Viteza scanare alb negru	Pana la 160 ipm (cu DF-701 optional)
Rezolutie scanare	Max.: 600 x 600 dpi

Imaginea este cu titlu de prezentare

Moduri scanare	Scan-to-eMail (Scan-to-Me) Scan-to-SMB (Scan-to-Home) Scan-to-FTP Scan-to-Box Scan-to-USB Scan-to-WebDAV Scan-to-DPWS Scanare TWAIN in retea	Casete hartie standard	Caseta 1:500 coli, A5-A3, 52-256 g/m <sup>2</sup> Caseta 2:500 coli, A5-SRA3, 52-256 g/m <sup>2</sup> Alimentare manuala (bypass): 150 coli, A6-SRA3, dimensiuni particularizate, banner, 60-300 g/m <sup>2</sup>
Formate fisier	JPEG; TIFF; PDF; PDF/A 1asi 1b (optional); PDF compact; PDF criptat; PDF indexabil (optional); XPS; XPS compact; PPTX; PPTX indexabil (optional); DOCX/XLSX indexabil (optional)	Casete hartie optional	Caseta 3:500 coli, A5-A3, 52-256 g/m <sup>2</sup> Casetele 3 +4: 2x500 coli, A5-A3, 52-256 g/m <sup>2</sup> Caseta de mare capacitate: 2,500 coli, A4, 52-256 g/m <sup>2</sup>
Destinatii scanare	2,100 (utilizatori + grupuri); suport LDAP	Duplex automat	A5-SRA3; 52-256 g/m <sup>2</sup> Offset; grupare; sortare; capsare; perforare; post inserare; pliere mediana; pliere in forma de scrisoare; brosurare
Functii scanare	Anotare (text/timp/data) pentru PDF; pana la 400 programe joburi; previzualizare scanare in timp real	Moduri finisare (optional)	
<b>Specificatii fax</b>		Capacitate iesire (cu finisher)	Max.: 3,300 coli
Standard fax	Super G3 (optional)	Capacitate iesire (fara finisher)	Max.: 250 coli 50 coli sau 48 coli + 2 coperti (pana la 209 g/m <sup>2</sup> )
Transmisie fax	Analog i-Fax i-Fax color (RFC3949-C) IP-Fax	Capsare	
Rezolutie fax	Max.: 600 x 600 (ultra-fine) dpi	Capacitate iesire la capsare	Max. 1,000 coli
Compresie fax	MH; MR; MMR; JBIG	Pliere in forma de scrisoare	Pana la 3 coli
Modem fax	Pana la 33,6 Kbps	Capacitate coli pliate in forma de scrisoare	Max.: 30 coli (tava); nelimitat Max.: 20 coli sau 19 coli + 1 coperta (pana la 209 g/m <sup>2</sup> )
Destinatii fax	2,100 (utilizatori + grupuri)	Brosura	Max.: 100 coli (tava); nelimitat
Functii fax	Polling; transmisie intarziata; PC-Fax; receptie confidentiala in box; Receptie pe e-mail/FTP/SMB; pana la 400 programe joburi	Capacitate iesire brosururi	Max.: 100 coli (tava); nelimitat
<b>Specificatii user box</b>		Volum copiere/printare recomandat (lunar)	25,000 pagini
Nr. maxim documente care se pot stoca	Pana la 3,000 documente sau 10,000 pagini	Volum copiere/printare maxim (lunar)	80,000 pagini
Tipuri de user box	Public Personal (cu parola sau autentificare) Grup (cu autentificare)	Durata viata toner Black	27000
Tipuri de boxuri sistem	Printare securizata Printare PDF criptat Receptie fax Fax polling	Durata viata toner CMY	25000
Functionalitati user box	Reprintare; combinare Descarcare Trimitere (e-mail/FTP/SMB si Fax) Copiere din box in box	Consum energie	220-240 V / 50/60 Hz Mai putin de 1.5 kW (sistem) 615 x 685 x 779 mm (fara ADF si casete suplimentare)
<b>Specificatii sistem</b>		Dimensiuni sistem (LxIxxH)	
Memorie sistem standard	2,048 (standard) MB	Greutate sistem	Aprox. 85 kg
Hard disk sistem standard	250 (standard) GB	<b>Functii sistem</b>	ISO15408 EAL3 (in evaluare), conform IEEE 2600.1, filtrare IP si blocare porturi, criptare comunicare in retea SSL2, SSL3 si TSL1.0, suport IPsec, suport IEEE 802.1x, autentificare utilizatori, raport autentificare, printare securizata, suprascriere hard disk (8 tipuri standard), criptare date pe hard disc (AES 128), stergere automata a datelor din memorie, receptiune confidentiala a faxurilor, protectie la copiere (copy guard, parola)
Interfete standard	10-Base-T/100-Base-T/1.000-Base-T Ethernet; USB 2.0	Securitate	Pana la 1.000 conturi utilizatori, suport Active Directory (nume utilizator + parola + email + folder smb) Definire acces utilizatori
Protocoale de retea	TCP/IP (IPv4 / IPv6); IPX/SPX; NetBEUI; Apple Talk (EtherTalk); SMB; LPD; IPP; SNMP; HTTP	Contorizare	Autentificare biometrica (scanarea dispunerii venelor in deget) optional Autentificare prin card IC-Card (cititor IC-Card ) optional
Tipuri frame-uri	Ethernet 802.2; Ethernet 802.3; Ethernet II; Ethernet SNAP	Software	PageScope Net Care Device Manager PageScope Data Administrator PageScope Box Operator PageScope Direct Print Print Status Notifier Driver Packaging Utility Log Management Utility
Alimentator automat documente	Pana la 100 originale; A6-A3; 35-163 g/m <sup>2</sup> RADF sau Dualscan ADF		
Format hartie	A6-SRA3, formate hartie particularizate; hartie banner max. 1,200 x 297 mm		
Greutate hartie	52-300 g/m <sup>2</sup>		
Capacitate alimentare hartie	Standard: 1,150 coli Max.: 6,650 coli		