

# KONICA MINOLTA Bizhub C450i

Simplu, conectat și sigur. Descoperiți bizhub i-Series!

- Viteza A4: 45 ppm color și alb-negru
- Formate hârtie: A6-SRA3, formate personalizate și imprimare banner până la 1,2 m
- Panou tactil color de 10,1 inch similar celui al tabletelor cu interfață de utilizator modernă, simplu de personalizat
- Detectare automată a mediilor de printare pentru o experiență îmbunătățită pentru utilizator
- Cel mai ridicat nivel de securitate a datelor datorită funcțiilor diverse de securitate, inclusiv motorul de antivirus Bitdefender, reduce riscul de pierdere a datelor și păstrează în siguranță datele confidențiale



Imaginea este cu titlu de prezentare



SPECIFICATII SISTEM	
System memory (standard/max)	8,192 MB (standard/max)
System hard drive	System hard drive 256 GB SSD (standard) / 1 TB SSD (optional)
Interface	10/100/1,000-Base-T Ethernet; USB 2.0;
Netw ork protocols	Wi-Fi 802.11 b/g/n/ac (optional) TCP/IP (IPv4 / IPv6); SMB; LPD; IPP; SNMP; HTTP(S); Bonjour
Frame types	Ethernet 802.2; Ethernet 802.3; Ethernet II; Ethernet SNAP
Automatic Document Feeder	Up to 300 originals; A6-A3; 35-210 g/m <sup>2</sup> ; Dualscan ADF
Printable paper size	A6-SRA3; customized paper sizes; banner paper max. 1,200 x 297 mm
Printable paper weight	52-300 g/m <sup>2</sup>
Paper input capacity (standard/max)	1,150 sheets / 6,650 sheets (standard/max)
Paper tray input (standard)	1x 500; A6-A3; custom sizes; 52-256 g/m <sup>2</sup>
Paper tray input (optional)	1x 500; A5-SRA3; custom sizes; 52-256 g/m <sup>2</sup>
	1x 500 sheets; A5-A3; 52-256 g/m <sup>2</sup>
	2x 500 sheets; A5-A3; 52-256 g/m <sup>2</sup>
	1x 2,500 sheets; A4; 52-256 g/m <sup>2</sup>
	1x 1,500 + 1x 1,000 sheets; A5-A4; 52-256 g/m <sup>2</sup>
Large capacity tray (optional)	1x 3,000; A4; 52-256 g/m <sup>2</sup>
	1x 2,500; A4-SRA3; custom sizes; 52-256 g/m <sup>2</sup>
	150 sheets; A6-SRA3; custom sizes; banner; 60-300 g/m <sup>2</sup>
Manual bypass	A6-SRA3; 52-256 g/m <sup>2</sup>
Automatic duplexing	A6-SRA3; 52-256 g/m <sup>2</sup>
Finishing modes (optional)	Offset; Group; Sort; Staple; Staple (offline); Punch; Half-fold; Letter-fold; Booklet; Post insertion; Z-fold

Output capacity (standard)	Max. 250 sheets
Output capacity (optional)	Max. 3,300 sheets
Stapling	Max. 100 sheets or 98 sheets + 2 cover sheets (up to 300 g/m <sup>2</sup> )
Stapling output capacity	Max. 200 sets
Letter fold	Max. 3 sheets
Letter fold capacity	Max. 50 sets; unlimited (w ithout tray)
Booklet	Max. 20 sheets or 19 sheets + 1 cover sheet (up to 300 g/m <sup>2</sup> )
Booklet output capacity	Max. 35 booklets; unlimited (w ithout tray)
Copy/print volume (monthly)	Rec. 40,000 pages; Max. <sup>2</sup> 200,000 pages
Toner lifetime	Black up to 28,000 pages CMY up to 28,000 pages
Imaging unit lifetime	Black up to 240,000/1,000,000 pages (drum/developer) CMY up to 155,000/1,000,000 pages (drum/developer)
Power consumption	220-240 V / 50/60 Hz; Less than 1.58 kW
System dimension (WxDxH)	615 x 688 x 961 mm (w ithout options)
System weight	Approx. 100.0 kg (w ithout options)
SPECIFICATII IMPRIMANTA	
Print resolution	1,800 (equivalent) x 600 dpi; 1200 x 1200 dpi
Page description language	PCL 6 (XL3.0); PCL 5c; PostScript 3 (CPSI 3016); XPS
Operating systems	Windows 7 (32/64); Windows 8.1 (32/64); Windows 10 (32/64); Windows Server 2008 (32/64); Windows Server 2008 R2; Windows Server 2012; Windows Server 2012 R2;

	Windows Server 2016; Windows Server 2019;
	Macintosh OS X 10.10 or later; Unix; Linux; Citrix
Printer fonts	80 PCL Latin; 137 PostScript 3 Emulation Latin
Mobile printing	AirPrint (iOS); Mopria (Android); Konica Minolta Print Service (Android); Konica Minolta Mobile Print (iOS/Android/Windows 10 Mobile) optional: Google Cloud Print; WiFi Direct
<b>SPECIFICATII IMPRIMANTA (OPTIONAL)</b>	
Print controller	Embedded Fiery IC-420
Controller CPU	AMD GX-424CC @ 2.4 GHz
Memory/HDD	4,096 MB / 500 GB
Page description language	Adobe PostScript 3 (CPSI 3020); PCL 6; PCL 5c
Operating systems	Windows 7 (32/64); Windows 8.1 (32/64); Windows 10 (32/64); Windows Server 2008 (32/64); Windows Server 2008 R2; Windows Server 2012; Windows Server 2012 R2; Windows Server 2016; Windows Server 2019; Macintosh OS X 10.10 or later; Linux
<b>SPECIFICATII SCANNER</b>	
Scan speed (mono/colour)	Up to 140/140 ipm in simplex (mono/colour)
	Up to 280/280 ipm in duplex (mono/colour)
Scan resolution	Up to 600 x 600 dpi
Scan modes	Scan-to-eMail (Scan-to-Me); Scan-to-SMB (Scan-to-Home); Scan-to-FTP; Scan-to-Box; Scan-to-USB; Scan-to-WebDAV; Scan-to-DPWS; Scan-to-URL; TWAIN scan
File formats	JPEG; TIFF; PDF; Compact PDF; Encrypted PDF; XPS; Compact XPS; PPTX
	optional: Searchable PDF; PDF/A 1a and 1b; Searchable DOCX/PPTX/XLSX
Scan destinations	2,000 destinations + 100 groups; LDAP support
<b>SPECIFICATII COPIATOR</b>	
Imaging technology	Laser
Toner technology	Simitri® HD polymerised toner
Copy/print speed A4 (mono/colour)	Up to 45/45
Copy/print speed A3 (mono/colour)	Up to 22/22
Autoduplex speed A4 (mono/colour)	Up to 45/45

1st copy out time A4 (mono/colour)	3.8/5.0 sec.
Warm-up time	Approx. 15/17 sec. (mono/colour) <sup>1</sup>
Copy resolution	600 x 600 dpi
Gradation	256 gradations
Multicopy	1-9,999
Original format	Max. A3
	25-400% in 0.1% steps; auto-zooming
Magnification	
<b>SPECIFICATII FAX</b>	
Fax standard	Super G3 (optional)
Fax transmission	Analogue; i-Fax; Colour i-Fax; IP-Fax
Fax resolution i	Up to 600 x 600 dp
Fax compression	MH; MR; MMR; JBIG
Fax modem	Up to 33.6 Kbps
Fax destinations	2,000 single + 100 groups
<b>SPECIFICATII USER BOX</b>	
Storable documents	Up to 3,000 documents or 10,000 pages
Type of user boxes	Public; Personal (with password or authentication); Group (with authentication)
Type of system boxes	Secure print; Encrypted PDF print; Fax receipt; Fax polling
<b>FUNCTII SISTEM</b>	
Security	ISO 15408 HCD-PP Common Criteria (in evaluation); IP filtering and port blocking; SSL3 and TLS1.0/1.1/1.2 network communication; IPsec support; IEEE 802.1x support; User authentication; Authentication log; Secure print; Kerberos; Hard drive overwrite; Hard drive data encryption (AES 256); Confidential fax; Print user data encryption optional: Antivirus realtime scanning (Bitdefender®); Copy protection (Copy Guard, Password Copy)
Accounting	Up to 1,000 user accounts; Active Directory support (user name + password + e-mail + smb folder); User function access definition; Authentication by mobile device (Android) optional: Biometric authentication (finger vein scanner); ID card authentication (ID card reader); Authentication by mobile device (iOS)
Software	Net Care Device Manager; Data Administrator; Box Operator; Web Connection; Print Status Notifier; Driver Packaging Utility; Log Management Utility