

KONICA MINOLTA Bizhub C287

Viteza A4/A3: 28/14 ppm alb-negru si color
Formate hartie: A6-A3 si formate personalizate
Model A3 color cu costuri de exploatare eficiente
Tehnologie de printare mobila de ultima generatie
Ideal pentru birouri mici
Printati de oriunde, oricand



Sisteme de operare



Imaginea este cu titlu de prezentare

Specificatii copiator

Proces copiere	Copiere laser, electrostatic, indirect
Sistem toner	Toner polimerizat Simitri® HD
Viteza copiere/printare A4 alb-negru (cpm)	Pana la 22 ppm
Viteza copiere/printare A4 color (cpm)	Pana la 28 ppm
Viteza copiere/printare A3 alb-negru (cpm)	Pana la 14 ppm
Viteza copiere/printare A3 color (cpm)	Pana la 14 ppm
Viteza duplex A4 alb-negru (cpm)	Pana la 28 ppm
Viteza duplex A4 color (cpm)	Pana la 28 ppm
Prima pag printata/copiata alb-negru (sec)	6,8
Prima pagina copiata/printata color (sec)	8,4
Timpul de incalzire (sec)	Approx. 20 (2)
Rezolutie copiere (dpi)	600 x 600
Gradatii	256 gradatii
Copiere multipla	1-9,999
Format documente originale	A5-A3
Marire-micsorare	25-400% in pasi de 0.1%; zoom automat
Functii copiere	Chapter; cover and page insertion; proof copy; adjustment test print; job setting memory; poster mode; image repeat; overlay (optional, with UK-211); stamping; copy protection

Specificatii imprimanta

Rezolutie printare (dpi)	1,800 (echivalent) x 600 dpi
Limbaje printare	PCL 6 (PCL 5c + XL 3.0) PostScript 3 (CPSI 3016) XPS
Sisteme operare	Windows VISTA (32/64) Windows 7 (32/64) Windows 8 (32/64) Windows 8.1 (32/64) Windows 10 (32/64) Windows Server 2008/2008 R2 (32/64) Windows Server 2012/2012 R2 (64) Macintosh OS X 10.x Linux
Fonturi printare	80 PCL Latin; 137 PostScript 3 Emulation Latin
Functii printare	Direct print of PCL; PS; TIFF; XPS; PDF (v1.4); encrypted PDF files and OOXML (DOCX; XLSX; PPTX); mixmedia and mixplex; "Easy Set" job programming; overlay; watermark; carbon copy print; copy protection
Printare mobila	AirPrint (iOS); Mopria (Android); Google Cloud Print (optional); Wi-Fi Direct (optional); Konica Minolta Print Service (Android); PageScope Mobile (iOS, Android); NFC Authentication and Pairing (Android)

Specificatii scanner

Viteza scanare color (opm)	Pana la 45 ipm
Viteza scanare alb-negru (opm)	Pana la 45 ipm
Rezolutie scanare (dpi)	Max.: 600 x 600

Moduri scanare	Scan-to-eMail (Scan-to-Me) Scan-to-SMB (Scan-to-Home) Scan-to-FTP Scan-to-Box Scan-to-USB Scan-to-WebDAV Scan-to-DPWS Network TWAIN scan	Duplex automat Moduri finisare (optional) Capacitate iesire (fara finisher) Capacitate iesire (w/o finisher) Stapling	A5-A3; 60-256 gsm Offset; group; sort; staple; punch; centre-fold; letter fold; booklet Max.: 3,300 coli Max.: 250 sheets Max.: 50 sheets or 48 sheets + 2 cover sheets (up to 209 gsm)
Formate fisier	TIFF; PDF; Compact PDF; JPEG; XPS; Compact XPS; DOCX; XLSX; searchable PDF; PDF/A; linearized PDF	Stapling output capacity Letter fold Letter fold capacity Booklet	Max. 1,000 coli Up to 3 sheets Max.: 30 coli (tray); unlimited Max.: 20 coli or 19 coli + 1 cover sheet (up to 209 gsm)
Destinatii scanare	2,100 (single + group); LDAP support	Booklet output capacity Volum copiere/printare recomandat (lunar)	Max.: 100 coli 13,000 pagini
Funcții scanare	Annotation (text/time/date) for PDF; up to 400 job programs; real-time scan preview	Volum copiere/printare maxim (lunar)	28,000 pagini (1)
Specificatii fax		Durata viata toner Black Durata viata toner CMY Durata viata developer Black Durata viata developer CMY Durata viata drum Black Durata viata drum CMY	24 21 600 600 105 90
Standard fax	G3	Consum energie	220-240 V / 50/60 Hz
Transmisie fax	Analogue i-Fax Colour i-Fax IP-Fax	Dimensiuni sistem (WxDxH, mm) Greutate sistem (kg)	Mai putin de 1.6 kW (system) 585 x 660 x 787 mm (main body) Approx. 72 kg (fara optionale/toner)
Rezolutie fax (dpi)	Max.: 600 x 600 dpi (ultra-fine)		
Compresie fax	MH; MR; MMR; JBIG		
Modem fax (Kbps)	Pana la 33.6 Kbps		
Destinatii fax	2,100 (single + group)		
Funcții fax	Polling; time shift; PC-Fax; receipt to confidential box; Receipt to e- mail/FTP/SMB; up to 400 job programs		
Specificatii sistem		Funcții sistem	
Memorie sistem standard (MB)	2,048 (standard)	Securitate	ISO 15408/IEEE 2600.2 compliant (in evaluation); IP filtering and port blocking; SSL2; SSL3 and TSL1.0 network communication; IPsec support; IEEE 802.1x support; user authentication; Authentication log; secure print; Hard disk overwrite (8 standard types); Hard disk data encryption (AES 256); Memory data auto deletion; Confidential fax receipt; Print user data encryption; copy protection
Hard disk sistem standard (GB)	250 (standard)		
Interfete standard	10-Base-T/100-Base-T/1,000-Base-T Ethernet; USB 2.0, Wi-Fi 802.11b/g/n (optional)	Contorizare	Up to 1,000 user accounts; Active Directory support (user name + password + e-mail + smb folder) User function access definition Biometric authentication (finger vein scanner) optional ID card authentication (ID card reader) optional
Protocoale de retea	TCP/IP (FTP; SMB; SMTP; WebDAV) (IPv4/IPv6)		
Tipuri frame-uri	Ethernet 802.2; Ethernet 802.3; Ethernet II; Ethernet SNAP		
Alimentator automat	Up to 100 originals; A6-A3; 35-128 gsm RADF optional available		
Format hartie	A5-A3; A6S; banner paper; Thick Paper X/Y size input range: Width: 90-297 mm; Length: 139.7-431.8 mm		
Greutate hartie (g/m ²)	60-256 gsm		
Capacitate alimentare hartie (coli)	Standard: 1,100 sheets Max.: 3,600 coli		
Casete hartie standard	Caseta 1: 500 coli; A5-A4; 60-256 gsm Caseta 2: 500 coli; A5-A3; 60-256 gsm Alimentare manuala (bypass): 100 coli; A6-A3; 60-256 gsm		
Specificatii hartie optional	Caseta 3: 500 coli; A5-A3; 60-256 gsm Caseta 3 + 4: 2 x 500 coli; A5-A3; 60- 256 gsm Large Capacity Cabinet: 2,500 coli; A4; 60-256 gsm Alimentare manuala (bypass): 100 coli; A6-A3; 60-256 gsm	Software	PageScope Net Care Device Manager PageScope Data Administrator PageScope Box Operator PageScope Direct Print Print Status Notifier Driver Packaging Utility Log Management Utility